





Ex II / III – Type Identification Key

<u>BS</u>	** 	<u>LED</u>	
	* 		
	* 		
	** 		
			<u>Max. Number</u> <u>LED Modules (COB) / Power Adjustable / Lumen Output at 5000 K</u> 52 - 2 / up to 30 Watt / 3360 lm (735 x 183 mm) 55 - 4 / up to 60 Watt / 6720 lm (1340 x 183 mm) 92 - 5 / up to 75 Watt / 8400 lm (1640 x 183 mm)
			<u>Enclosure</u> 5 - Aluminium profile with headpieces of plastic 6 - Steel sheet 7 - Stainless steel sheet 8 - Aluminium sheet, plastic powder coated 9 - Plastic profile with headpieces of plastic (for luminaires up to 1340 mm length)
			<u>Connections: Bores/Sleeves with Blind Plugs</u> 1 - 2x M 16 x 1.5 2 - 2x M 20 x 1.5 3 - 2x M 25 x 1.5
			<u>Connections: Plug-In Connectors</u> 4 - Plug/socket 5 - Plug/socket with line end unit 6 - Socket/plug with line end unit 7 - Plug 1x M 36 x 1.5 8 - Socket 1x M 36 x 1.5 9 - Plug with line end unit / 1x M 36 x 1.5 0 - Socket with line end unit / 1x M 36 x 1.5
			<u>Special Versions</u> 00 - No special version (IIB-LED module; riveted, lenses non-bonded) 01 - IIC-LED module; riveted or screwed, lenses bonded 02 - 00 with throughwiring 03 - 01 with throughwiring 07 - Luminaire for pole mounting